

Weld Protection Spray

Description

Prevents adhesion of welding beads on the workpiece and the torch without impairing the weld. Increases the service life of the welding nozzles and the inner components of the torch. Does not contain silicone or CFCs.

Properties

- prevents adhesion of welding beads on the workpiece and the torch
- does not contain CFCs
- silicone-free
- suitable for steel, aluminum and stainless steel
- increases service life

Technical data

Color / appearance	weiß / white
Form	flüssig, aerosol / liquid, aerosol
Propellant	Propan, Butan / propane, butane
Base	Talk / talc
Density	0,67 g/cm ³ DIN 51757
Solubility in water	unlöslich / insoluble
Odor	charakteristisch / characteristic
Flash point	-60 °C

Areas of application

Used for all welding work on steel, aluminium and stainless steel.

Application

Briefly shake aerosol can. Switch off the welding equipment and spray a thin coat on cold workpieces and torches.

Note: Do not spray onto workpieces or parts of the torch while still hot or glowing! Allow an airing time of at least 5 minutes.

Comment

Shake can regularly before extensive use. After use, clear spray nozzle (hold can with spray head upside down) by spraying until only pure propellant emerges.



Available pack sizes

500 ml Can aerosol	4086
	D-GB-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.